

# Phenomenal Brands



## Product Guide

### General Information

Minimum order requirement is \$250.  
Each product is identified by size and color with a case code number. Please use this number when ordering.

### Order Codes

DAP manufacturer's code No: 70798

### Customer Service Information

Call our Customer Service Department for assistance on order placement, deliveries, billing inquiries and authorization to return materials.

### Mail correspondence and confirming purchase orders to:

DAP Products Inc.  
2400 Boston Street, Suite 200  
Baltimore, MD 21224  
Fax order to: 410-558-1068

### Customer Service Department

800-DAP-3339  
410-675-2100  
(8:00 a.m. – 6:00 p.m. Eastern Time)

### International Customer Service

800-DAP-3339  
410-675-2100  
(8:00 a.m. – 6:00 p.m. Eastern Time)

### Technical Customer Service

888-327-8477 or 888-DAP-TIPS  
(8:00 a.m. – 6:00 p.m. Eastern Time M-F  
9:00 a.m. – 6:00 p.m. Sat.)

### Corporate Office

800-543-3840  
410-675-2100

### Supplemental Price Lists

For a copy of a current price list and conditions of sale, please contact your sales representative.

### SDS Requests

To obtain an SDS for any DAP product, please visit our website [www.dap.com](http://www.dap.com) or call 888-DAP-TIPS.

### Reduce Environmental Impact by Choosing Low VOC Content Products



DAP is dedicated to the development of adhesives and sealants with low volatile organic compound (VOC) content. Many of our products actually have a low enough VOC content, indicated by this symbol, to meet one or more of the guidelines outlined below:

- The South Coast Air Quality Management District (SCAQMD) Rule # 1168
- The Bay Area Air Quality Management District Regulation 8, Rule 51
- U.S. Green Building Council® LEED® - NC Green Building Rating System for New Construction & Major Renovations Version 2.2, EQ Credit 4.1 (Indoor Environmental Quality – Low Emitting Materials: Adhesives & Sealants)
- NAHB Model GREEN Home Building Guideline Section 7.1.3 (Global Impact - Products)

### Increase Energy Efficiency by Sealing the Building Envelope



In order to meet green building guidelines for energy efficiency you will need to take an integrated and comprehensive approach to an energy efficient design of the building site, the building envelope and mechanical space conditioning systems. Utilize products highlighted with this symbol when sealing the building envelope in accordance with the following guidelines:

- U.S. Green Building Council® LEED® - NC Green Building Rating System for New Construction and Major Renovations Version 2.2, EA Prerequisite 2 for Minimum Energy Performance. (Energy & Atmosphere – Minimum Energy Performance)
- NAHB Model GREEN Home Building Guidelines Section 3.3.1 Building Envelope (PP) B. (Energy Efficiency – Implement an Integrated and Comprehensive Approach to Energy – Efficient Design of Building Site, Building Envelope and Mechanical Space Conditioning Systems)
- ANSI/ASHRAE/IESNA Standard 90.1-2004 – Energy Standard for Buildings Except Low Rise Residential Buildings SI Edition – Section 5.4 and 5.5 (Building Envelope)

**Phenoseal® Caulks & Sealants**



**One Phenomenal Sealant®**



**Phenoseal®  
Vinyl Adhesive Caulk**

does it all!

A versatile all-purpose caulk, Phenoseal® Vinyl Adhesive Caulk is perfect for almost any job. It truly does it all — BONDS, CAULKS and SEALS. As an adhesive, it creates a strong bond; as a caulk, it contracts and expands to seal joints up to 1/4", as a sealant, it keeps water and air from penetrating cracks and seams preventing energy loss. This fast-drying interior/exterior formula cleans easily with soap and water. Cured caulk is mold and mildew resistant and can be painted with latex and oil-based paint.



Case Code	Size	Color	Product Code	Case Weight (lbs.)	Case Pack	Case Dimensions LxWxH	Case Volume (cu.ft.)	UPC Check Digit	Cases per Pallet
00005	10 FL. OZ.	White	00005	11.46	12	8" x 6" x 11.75	0.33	1	108
00524	10 FL. OZ.	White	00005	22.95	24	12" x 8.5" x 12	0.71	1	54
00101	5.5 FL. OZ.	White	00101	6.40	12	10.5" x 4.5" x 10.5"	0.29	0	99
00006	10 FL. OZ.	Translucent	00006	10.29	12	8" x 6" x 11.75	0.33	8	108
01101	5.5 FL. OZ.	Translucent	01101	5.69	12	10.5" x 4.5" x 10.5"	0.29	0	99
02102	10 FL. OZ.	Almond	02102	11.58	12	8" x 6" x 11.75	0.33	5	108
04102	10 FL. OZ.	Metal Gray	04102	11.58	12	8" x 6" x 11.75	0.33	3	108
06102	10 FL. OZ.	Black	06102	11.58	12	8" x 6" x 11.75	0.33	1	108
09102	10 FL. OZ.	Brown	09102	11.58	12	8" x 6" x 11.75	0.33	8	108

**Phenoseal® Does It Clear®  
Acrylic Latex  
Adhesive Caulk**

Phenoseal® Does It Clear!® Acrylic Latex Adhesive Caulk is a water-based caulk ideal for use wherever an invisible seal is desired. It can be used for a variety of interior and exterior applications and provides a weatherproof seal with easy soap and water clean-up. Does It Clear!® won't crack or discolor with age and may be scrubbed with most household cleansers. The cured caulk is mold and mildew resistant.



Case Code	Size	Color	Product Code	Case Weight (lbs.)	Case Pack	Case Dimensions LxWxH	Case Volume (cu.ft.)	UPC Check Digit	Cases per Pallet
00602	10 FL. OZ.	Crystal Clear	00602	9.87	12	8" x 6" x 11.75"	0.33	2	108

**Phenopatch® Repair** Products



**One Phenomenal Repair®**





## PATCH-N-PAINT® Lightweight Spackling (RTU)

PATCH-N-PAINT® lets you patch and prime in one easy step, saving time and money. It dries fast with no need to sand or prime, letting you paint in minutes. The advanced, lightweight formula with Microsphere Technology, provides an ultra smooth surface for the painting and hiding of the repair. Won't crack or shrink. Easy one-stroke application. Interior/exterior use.



Case Code	Size	Color	Product Code	Case Weight (lbs.)	Case Pack	Case Dimensions LxWxH	Case Volume (cu.ft.)	UPC Check Digit	Cases per Pallet
01602	1/2 PT.	WHITE	01502	7.50	24	13.75" x 10.5" x 6.75"	0.61	9	66
01611	1 QT.	WHITE	01511	8.75	8	10.5" x 10.5" x 10.25"	0.64	1	64
01517	1 GAL.	WHITE	01517	8.50	2	16" x 8" x 8.25"	0.61	3	75

## All-Purpose Spackling Paste (RTU)

All-purpose, heavyweight spackling compound for repairing and filling cracks and holes in wallboard, drywall, plaster, wood, brick and stone. It spreads smoothly, sands easily and resists cracking for fast professional repairs. Interior/exterior use.



Case Code	Size	Color	Product Code	Case Weight (lbs.)	Case Pack	Case Dimensions LxWxH	Case Volume (cu.ft.)	UPC Check Digit	Cases per Pallet
10222	1/2 PT.	WHITE	76858	25.50	24	13.75" x 10.5" x 6.75"	0.56	1	66
10224	1 QT.	WHITE	76857	32.75	8	10.5" x 10.5" x 10.25"	0.64	4	64
76859	1 GAL.	WHITE	76859	33.00	2	16" x 8" x 8.25"	0.61	8	75

## CUSTOM FLEXIBLE PATCH™ Pro-Grade Elastomeric Patching Compound- Smooth (RTU)

A high-performance, elastomeric pro-grade patching, sealing and bridging compound for repairing recurring cracks in wood, masonry, stucco, drywall and plaster. It is 50% more flexible than traditional vinyl and acrylic spackling compounds to expand and contract with surface movement and prevent cracks from reappearing. Won't shrink or crack. Provides excellent paintability and won't gloss paint. Smooth finish. Interior/exterior use.



Case Code	Size	Color	Product Code	Case Weight (lbs.)	Case Pack	Case Dimensions LxWxH	Case Volume (cu.ft.)	UPC Check Digit	Cases per Pallet
1227	10.1 FL OZ.	WHITE	12274	14.75	12	8" x 6" x 11.75"	0.33	1	108
14611	1 QT.	WHITE	12611	27.50	8	10.5" x 10.5" x 10.25"	0.64	4	64
12617	1 GAL.	WHITE	12617	27.25	2	16" x 8" x 8.25"	0.61	6	75

## Spackling Repair Products



### CUSTOM FLEXIBLE PATCH™ Pro-Grade Elastomeric Patching Compound- Textured (RTU)

A high-performance, elastomeric pro-grade patching, sealing and bridging compound for repairing recurring cracks in wood, masonry, stucco, drywall and plaster. It is 50% more flexible than traditional vinyl and acrylic spackling compounds to expand and contract with surface movement and prevent cracks from reappearing. Won't shrink or crack. Provides excellent paintability and won't gloss paint. Textured finish. Interior/exterior use.



Case Code	Size	Color	Product Code	Case Weight (lbs.)	Case Pack	Case Dimensions LxWxH	Case Volume (cu.ft.)	UPC Check Digit	Cases per Pallet
12284	10.1 FL OZ	OFF-WHITE	12284	12.75	12	8"x 6"x 12"	0.33	0	108
14717	1 GAL.	OFF-WHITE	12717	22.00	2	16"x 8"x 8.25"	0.61	3	75

## Joint Treatment Products



### Premium Lightweight Joint Compound with DRYDEX® Dry Time Indicator (RTU)

A premium, pre-mixed joint compound for the ultra smooth, high quality finishing of gypsum panel joints, nail head and metal corner beads. Easy handling, lightweight formula goes on PINK and dries WHITE indicating when additional coats can be applied or when it's ready for finishing. De-aired formula eliminates the formation of pinhole bubbles for an ultra-smooth finish. Sands effortlessly and produces 50% less airborne dust than other heavyweight joint compounds for less mess and faster clean-up. Interior use.



Case Code	Size	Color	Product Code	Case Weight (lbs.)	Case Pack	Case Dimensions LxWxH	Case Volume (cu.ft.)	UPC Check Digit	Cases per Pallet
10225	1 GAL.	WHITE	10125	21.50	2	16" x 8" x 8.25"	0.61	8	75

### Wallboard Joint Compound (RTU)

A pre-mixed, professional grade compound for taping, finishing and texturing interior gypsum wallboard. It can be used to cover and finish gypsum wallboard joints, embed reinforcing tape, metal corner beads, screw or nail holes. It is easy to apply, has minimal shrinkage and sands easily.



Case Code	Size	Color	Product Code	Case Weight (lbs.)	Case Pack	Case Dimensions LxWxH	Case Volume (cu.ft.)	UPC Check Digit	Cases per Pallet
00411	3 LB.	OFF-WHITE	00111	25.75	8	10.5" x 10.5" x 10.5"	0.64	4	64
00417	12 LB.	OFF-WHITE	00117	30.25	2	16" x 16" x 8.25"	0.61	6	75

## Stucco Repair Products



### Pre-Mixed Stucco Patch (RTU)

An easy-to-use patching compound for repairing minor cracks and breaks in stucco. It creates a hard durable patch which when painted, blends evenly with the original stucco. Textured finish. Interior/exterior use.



Case Code	Size	Color	Product Code	Case Weight (lbs.)	Case Pack	Case Dimensions LxWxH	Case Volume (cu.ft.)	UPC Check Digit	Cases per Pallet
64811	1 QT.	OFF-WHITE	60811	34.50	6	10.5" x 10.5" x 5.25"	0.64	5	64
60817	1 GAL.	OFF-WHITE	60817	32.00	2	16" x 8" x 8.25"	0.61	7	75

## Plaster Repair Products



### FLEXALL™ Pro-Grade All-Purpose Patch (RTU)

An all-purpose, pro-grade pre-mixed bridging and patching compound that dries flexible to prevent cracks from reappearing. It can be used to repair cracks in wood, metal, stucco, plaster, concrete and tile. Sandable. Interior/exterior use.



Case Code	Size	Color	Product Code	Case Weight (lbs.)	Case Pack	Case Dimensions LxWxH	Case Volume (cu.ft.)	UPC Check Digit	Cases per Pallet
34011	1 QT.	WHITE	33011	27.00	8	10.5" x 10.5" x 10.25"	0.64	5	64
33017	1 GAL.	WHITE	33017	27.00	2	16" x 8" x 8.25"	0.61	7	75

## Concrete Repair Products



### Pre-Mixed Concrete Patch (RTU)

A high-strength patching compound for repairing cracks or breaks in concrete and mortar joints. It can also be used to patch and spot level interior or exterior concrete and masonry surfaces. It dries to a durable, hard finish. Provides a non-shrinking patch. Easy water clean-up.



Case Code	Size	Color	Product Code	Case Weight (lbs.)	Case Pack	Case Dimensions LxWxH	Case Volume (cu.ft.)	UPC Check Digit	Cases per Pallet
32611	1 QT.	GRAY	32611	33.10	8	10.5" x 10.5" x 5.25"	0.64	8	64
32617	1 GAL.	GRAY	32617	33.10	8	16" x 8" x 8.25"	0.61	0	75





Phenoseal®, Does It All®, Does It Clear!® and One Phenomenal Sealant® are registered trademarks of Gloucester Co., Inc.

Phenopatch®, One Phenomenal Repair®, One Phenomenal Sealant® and Patch-N-Paint® are registered trademarks of DAP Brands Company.

Custom Flexible Patch™, Flexall™ and Simply Phenomenal™ are trademarks of DAP Brands Company.

#### PHENOMENAL BRANDS

A division of DAP Products Inc.  
2400 Boston Street, Suite 200  
Baltimore, MD 21224  
410-779-3265

An **RPM** Company

